


	SERIES	٥.	02		04				
DEX PLATES	Type MECA / NUM	• / o	•/•	• / •	o / •	o / •			
	Molding machines compatibility [T]	50 - 100	100 - 300	250 - 500	400 - 1000	800 - 2200			
	Number of positions	2 - 3 / -	2 - 3 / infinity	2 - 3 / infinity	- / infinity	- / infinity			
	180° Rotation time [s]	1.2	0.6	0.7	0.7	1			
	Max operating temperature [°C]	100°C / -	100°C / 75°C	100°C / 75°C	- / 75°C	- / 75°C			
	Index Plate Size [mm]	Fitted to molding machine moving plate							
Z	Index Plate thickness [mm]	150	180	230	270	350			
	Mold max weight (fixed part) [kg]	Equal to molding machine moving plate max weight							
	Max mold weight (moving part) Shaft in [kg]	150 / -	650 / 750	1400 / 2000	- / 3500	- / 7000			
	Standard shaft stroke [mm]	100	150	250	300	400			



	SERIES	G1	G2	G3	G4	G5		
	Rotary links - water - # of circuits	2	2 - 4	4 - 6	4 - 6	4 - 6		
	Rotary links - oil / air / electricity	•/•	• / •	•/•	o / •	o / •		
	Double shaft	0/0	0/•	o / •	o / •	o/•		
S	Pharma - ISO 7 class	0/•	0/•	o / •	o / •	o / •		
OPTIONS	Integrated magnetic plate	0/0	• / •	• / •	o / •	o / •		
9	LSR & Silicon compatibility	0/0	• / o	• / o	0/0	0/0		
	Integrated ejection system	• / o	• / •	• / •	o / •	o / •		
	Mold quick clamping system	upon request						
	Partial or Full integration in Molding Machine	Available according to molding machine brand						